


DOOR VIEWERS

SECURITY HARDWARE

DOOR VIEWERS



B02

- Solid brass door viewer
- Acrylic optical lens
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	ø BORE	FIRE RATING	VISION ANGLE	/BOX
B02	C3, C26D	1 3/8 – 2 1/4 (35–57)	12 mm	—	160°	25
B03	C3, C26D		14 mm	—	180°	25
B04	C3, C26D		16 mm	—	200°	10

IN (MM)



DV160



DV180, DV200

- Solid brass door viewer
- cULus 20 minute fire rating for labelled fire doors
- Polished glass and acrylic optical lenses
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	ø BORE	FIRE RATING	VISION ANGLE	/BOX
DV160	3, 26, 26D	1 3/8 – 2 (35–51)	12 mm	20 min	160°	25
DV180	26D		14 mm	20 min	180°	25
DV200	26D	1 3/8 – 2 1/4 (35–57)	14 mm	20 min	200°	10

IN (MM)



DV1012SRG



DV1012BRQ



DV1012BLQ

- Solid brass door viewer
- cULus 90 minute fire rating for labelled fire doors
- Polished glass and quartz lens
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	ø BORE	FIRE RATING	VISION ANGLE	/BOX
DV1012SRG	15, 19, 26D	1 1/16 – 1 1/8 (17.5–27)	12 mm	90 min	160°	25
DV1012BRQ	26	1 3/8 – 2 (35–51)	12 mm	90 min	160°	42
DV1012BLQ	19, 26	1 3/4 – 2 1/4 (44.5–57)	12 mm	90 min	200°	25
DV1014BLQ	15, 19, 26D		14 mm	90 min	200°	25

IN (MM)



DV1016LG

- Solid brass door viewer
- UL 20 minute fire rating
- Polished optical glass lenses
- Individually boxed

MODEL	FINISH	DOOR THICKNESS	ø BORE	FIRE RATING	VISION ANGLE	/BOX
DV1016LG	26D	1 3/8 – 2 1/4 (35–57)	16 mm	20 min	200°	25


IN (MM)

DOOR VIEWERS

SECURITY HARDWARE

REVOLVING DOOR VIEWER

511




- Revolving door viewer
- Stamped brass components
- Crystal optical glass lenses
- Individually boxed
- 511 KTD Extension kit available for 2" (50.3 mm) thick doors

MODEL	FINISH	DOOR THICKNESS	Ø BORE	FIRE RATING	VISION ANGLE	/UNIT
511	C3, C26D, C19	1 3/8 – 1 3/4 * (35–44)	2 3/8 (60.3)	—	140°	1

IN (MM) *UP TO 2" (50.3 MM) WITH EXTENSION KIT

REFLEX DOOR VIEWER

DS1000, DS2000



- Reflex door viewer with 2" (50.3 mm) screen
- Warnock Hersey listed for 20 minutes fire rated location when used with firestop sealant (not supplied) on a wood composite fire door
- Precision optics, no image distortion, clear viewing up to 7 feet away
- Individually carded

MODEL	FINISH	MATERIAL	DOOR THICKNESS	Ø BORE	FIRE RATING	VISION ANGLE	/UNIT
DS1000	BL, BR, GR	ABS plastic	1 3/8 – 2 (35–51)	2 3/8 (60.3)	20 min	132°	1
DS2000	SL, BL	Aluminum					


IN (MM)

DOOR VIEWER – LARGE

DS300



DS300CHR-COVER



- Zinc die cast door viewer
- Polished glass optical lens
- Viewer is intended for use with classified fire door rated up to and including 90 minutes
- Detachable lens cover is included
- Individually boxed
- Replacement lens cover: #DS300CHR-COVER

MODEL	FINISH	DOOR THICKNESS	Ø BORE	FIRE RATING	VISION ANGLE	/BOX
DS300	BP, CHR	1 3/8 – 2 (35–51)	3 1/32 (24.5)	90 min	180°	15

IN (MM)

