
KEY CABINETS

SECURITY HARDWARE

KEY CABINET





- Sturdy all metal construction with rounded corners allow for greater strength and durability
- Heavy gauge seamless steel
- Scratch-resistant light grey paint
- Rust proof
- Complete with key hooks, key tags, 2 screws and plugs
- Pre-slotted mounting holes
- Lockable cabinet standard KD version, KA version available with purchase of replacement CL50 keyed alike cam locks (see below), 2 keys per cabinet / cam lock supplied



CL50

- Replacement cam lock for 50 series key cabinet
- Key is removable in locked or unlocked position with 90° angle rotation
- Suitable for panel thickness up to 3/32" (2.4 mm)
- Available keying KA1, KA2, KD



KB50 / KB50-2


- 4 pins
- Nickel plated brass key blank
- Available keyway 101 & 102

MODEL	NUMBER OF KEY HOOKS	А	В	С	/CASE
50-20	20	9 % (250)	7 1/8 (180)	3 1/8 (80.5)	12
50-40	40				8
50-50	50	11 ¹³ / ₁₆ (300)	91/8	3 %16 (90)	6
50-70	70		(230)		8
50-105	105	14 3 / ₁₆ (360)		43/8 (110)	
50-120	120		9 % (250)		6
50-140	140		(250)		

IN (MM)

EMERGENCY BOX





- Sturdy heavy gauge steel construction
- Scratch resistant, painted red
- Single key hook
- Includes steel hammer-rod and cord
- Lockable cabinet; 2 keys supplied
- Pre-drilled mounting holes
- Includes wood screws and plastic anchors
- #EB02G: Replacement glass

MODEL	А	В	С	/CASE
EB-02	5 29/32 (150)	4 ¹⁷ / ₉₂ (115)	1 <mark>%16</mark> (40)	25

KEY RINGS


SECURITY HARDWARE

SPLIT KEY RINGS



20600 / TKR






- Strong tempered spring steel split ring (20600 and TKR series)
- Strong tempered steel light-duty split ring (P412 series)
- Finish: nickel plated

MODEL	øA	В	/ BOX¹	/ CASE ²
20616	5 /8 (16)	3 /64 (1.2)	100	500
20619	3 / ₄ (19)	1 /16 (1.6)	100	1000
20623	7 ∕8 (22)	1/16 (1.6)	100	1000
20625	1 (25)	1/ ₁₆ (1.6)	100	1000
20628	11/8 (28.3)	1/16 (1.6)	100	500
20632	1% (32.2)	5/64 (2.0)	100	500
20635	1 3 / ₈ (35.2)	5/64 (2.0)	100	500
20638	1½ (38)	5/64 (2.0)	100	500
20645	13/4 (45)	3/32 (2.4)	50	400
20651	2 (51)	3/ ₃₂ (2.4)	50	200
TKR16	2 3 / ₁₆ (55)	3 / ₃₂ (2.4)	_	50
TKR24	3 (76)	½ (3.2)	_	25
P412A	5 /8 (16)	1/16 (1.6)	10,000	40,000
P412B	1 (25)	1/16 (1.6)	1,000	20,000

IN (MM) (1) UNITS PER BAG (2) UNITS PER CASE


PULL-APART KEY RING



- Pull-apart tempered steel key ring
- Finish: nickel plated

MODEL	øA	В	/ BOX	
PAR3	3 ¾ (95)	1/8(3.1)	25	
PAR4	5 (127)	1/8(3.1)	25	
PAR6	6 (152)	1/8(3.1)	25	
IN (MM)				

HOOK KEY RING



• Tempered steel hook key ring

MODEL	А	øΒ	С	D	/ BOX
CP4	2 ¹¹ / ₁₆ (68.6)	1 %1 6 (39.7)	11/ ₁₆ (17.6)	1/ ₈ (3)	100

IN (MM)